



TECHNICAL SPECIFIC

DOORS

- 1x roll-up door (2x 12m wide for each 100 sqm of floor)
- Roll-up doors equipped with hydraulic system (2000 kg capacity, 1000 kg capacity, 1000 kg capacity)
- Roll-up doors equipped with hydraulic system (2000 kg capacity, 1000 kg capacity, 1000 kg capacity)

FACADE

- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation

ROOF

- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation

SUPPORTING STRUCTURE

- Steel frame structure, height 10m
- Steel frame structure, height 10m
- Steel frame structure, height 10m

PRODUCTION UPGRADE

- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation
- Horizontal window system with manual and automatic operation



OUTSIDE AREAS

- Hard space from concrete slabs, covered by gravel
- One high space from concrete slabs, covered by gravel
- One high space from concrete slabs, covered by gravel

OFFICES

- 2x2x2 office designed for 100 people, with office, kitchen, restrooms, and shower
- 2x2x2 office designed for 100 people, with office, kitchen, restrooms, and shower
- 2x2x2 office designed for 100 people, with office, kitchen, restrooms, and shower


FLOOR

- Steel frame structure, height 10m
- Steel frame structure, height 10m
- Steel frame structure, height 10m

HALL INSTALLATIONS

- One office, kitchen, restrooms, and shower
- One office, kitchen, restrooms, and shower
- One office, kitchen, restrooms, and shower

Panattoni Park Stribro




	Building 1	Building 2	Building 3	Building 4
AREA	1000 m²	1000 m²	1000 m²	1000 m²
HEIGHT	10 m	10 m	10 m	10 m
LOAD BEARING	10 kN/m²	10 kN/m²	10 kN/m²	10 kN/m²