



TECHNICAL SPECIFICATION

DOORS	FACADE	ROOF	SUPPORTING STRUCTURE	PRODUCTION UPGRADE
1x roll-up door 12x12m for main 1000 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift	2x roll-up door 12x12m for main 1000 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift	2x roll-up door 12x12m for main 1000 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift	2x roll-up door 12x12m for main 1000 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift	2x roll-up door 12x12m for main 1000 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift 2x roll-up door 6x6m for secondary 500 kg lift